



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .












HRS DRAWING FOR REFERENCE


RECOMMENDED PCB PATTERN, MOUNTING SIDE(4:1)

t=1



NOTE 1 THE CO-PLANARITY OF LEADS AND METAL SHELLS SHALL BE $0^{+0.05}_{-0.1}$.

SET MOUNTED EXAMPLE



TO
Q1

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
2	PHOSPHOR BRONZE	SELECTIVE GOLD PLATING 1.27μm			
1	PPS	(BLACK) UL94V-0	3	COPPER ALLOY	TIN PLATING 1μm

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	M. Itano 06·1·17	F. Taniguchi 06·1·17	Y. Enami 06·1·17	C. Miwa 06·01·17	. .

SCALE	DRAWING NO.	PART NO.
2 : 1	EDC3-122138-01	TM18R-TO-88(50)
UNITS mm	HIROSE ELECTRIC CO., LTD	CODE NO. CL222-2883-9-50

1/1

FORM NO.2891