

APPLICABLE STANDARD						
RATING	OPERATING TEMPERATURE RANGE	-25°C TO 60°C	STORAGE TEMPERATURE RANGE	-25°C TO 60°C		
	VOLTAGE		CURRENT			
SPECIFICATIONS						
ITEM		TEST METHOD	REQUIREMENTS		QT	AT
CONSTRUCTION						
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.		X	X
MARKING		CONFIRMED VISUALLY.			X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
△	1	DIS-E-00002932	KIM JAEHYEON	TU. TANIGUCHI	20200403	
REMARK			APPROVED	HO. MIWA	20050105	
			CHECKED	TH. KAMEYA	20050105	
			DESIGNED	SS. SATOH	20050105	
			DRAWN	SS. SATOH	20050105	
Unless otherwise specified, refer to IEC 60512. △						
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-122818-11-01	
HRS	SPECIFICATION SHEET		PART NO.	TM11BP-8-CV (1*)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL 222-2898-6-1※		△ 1/1