

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△						△						
△						△						
APPLICABLE STANDARD												
RATING	OPERATING TEMPERATURE RANGE		-55 °C TO 80 °C			STORAGE TEMPERATURE RANGE		— °C TO — °C				
	VOLTAGE		—			OPERATING HUMIDITY RANGE		— % TO — %				
	CURRENT		—			APPLICABLE CABLE		DIAMETER 7.5mm MAX				
SPECIFICATIONS												
ITEM		TEST METHOD				REQUIREMENTS				QT	AT	
CONSTRUCTION												
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				○	○	
MARKING		CONFIRMED VISUALLY.								○	○	
MECHANICAL CHARACTERISTICS												
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.76 mm, - m/s ² AT 2 h, FOR 3 DIRECTIONS.				NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				○	—	
SHOCK		490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 3 DIRECTION.								○	—	
ENVIRONMENTAL CHARACTERISTICS												
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				○	—	
REMARKS												
DRAWN						DESIGNED	CHECKED	APPROVED	RELEASED			
A.KUBO						98.9.22	98.9.22	98.9.22	98.9.24			
Unless otherwise specified, refer to JIS C 5402.												
Note QT:Qualification Test AT:Assurance Test ○:Applicable Test												
HRS HIROSE ELECTRIC CO., LTD.						SPECIFICATION SHEET						
CODE NO.(OLD)						PART NO.						
CL						DX-28-CV1						
DRAWING NO.						CODE NO.						
ELC4-040769						CL-230-0055-0						
						1/1						

