		notive equipment / device which demand high reliability, kindly contact our sales window correspondents.
		nde
		odse
		00
		§ 9
	•	<u>ĕ</u>
	-	y, kindly contact our sales window corresponder
.		S IN
e S	•	act c
Ses	•	Sonta
nts		<u>a</u> ∫
20		, Z
₹.		
	:	ellak
Ď,	-	ghr
$\frac{3}{2}$	-	בֿ
2		¥ W
H	-	ž
24 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.	-	ve equipment / device which demand higr
₹		<u> </u>
24 F		ge/
t 20	•	ent
yrig		⊿din
500		ed e
)24	•	otič
12		Jton
Mag		og F
	•	nsir
		יסלר
	•	atio
		sidel
		cou
		e ot
		cas
	-	_

				_			1	7 1				T	T1		
	COUNT	DESCRIPTION	OF REVIS	SIONS	BY	CHKD	DATE	1	COUNT	DESCRIPTION O	F REVISIONS	BY	CHKD	DA	TE
								\triangle							
]									
API	PLICA	BLE STAND	DARD												
OPERATING TEMPERATURE RANGE -55 °C						СТ	TO 00 00 1			AGE ERATURE RANGE		°C TO — °C			
RATING VOLTAGE			TO THE STATE OF TH					OPER	ATING HUMIDITY		- % TO -			/ / ₀	
			RANG					U CARLE CARLE					/0		
CURRENT										MAX φ 9.4					
SPECIFICATIONS															
	ITEM TEST METHOD REQUIREMENTS QT A											AT			
		UCTION													
		XAMINATION								ACCORDING TO	DRAWING.			0	
MAF	RKING		VISUALI	Y AND	BY M	EASU	RING INST	RUMEN	Т.					0	
ME	CHAN	IICAL CHA													
VIBF	RATION						Hz, SINC m/s² A			NO DAMAGE, CR OF PARTS.	ACK AND LO	OSEN	ESS,		-
			FOR 3				111/5 A		"	OF FARTS.					
SHC	СК		490 m/s ²	DIREC	TION	S OF P	ULSE 11	ms A1	Г 3					0	_
EVI	VIROI	NMENTAL	CHAR			ECTIC									J
		SALT MIST						RAY FC	R I	NO DAMAGE, CR	ACK AND LO	OSEN	ESS,	10	T
			ſ	3 h.						OF PARTS.			·	\perp	<u> </u>
ļ															
															ĺ
l													Ì		
1															I
İ													1		
															l
REN	MARKS							D	RAWN	DESIGNED	CHECKED	APPR	OVED	RELEA	ASED
								1	116			low	,		
								U.	photo	[a.K.L.]	4. Escame	$\mathcal{H}\mathcal{H}$	arm		
Unless otherwise specified, refer to JIS C 5402.							a.K.to 19.11.X	J , 5	99	15					
									/	1111111	[∃, U \ 7			L	
Note		alification Test	AT:ASS	urance	rest	T	olicable Tes			PART N	D.				
IT.	HIS HIROSE ELECTRIC CO., LTD. SPECIFICATION SHEET DX-50-CV1														
	E NO.(OL	D)						CO	CODE NO.					1/	
	CL		ELC4-040136							CL230-0057-6					