Feb.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Mated (4:1)





2 Recommended PC Board Pattern (Mounting side)











HRS DRAWING FOR REFERENCE

Note 1. Lead coplanarity to be 0.1 max.

2 All dimentions without tolerance are dimentions forreference.

3 Plating
Contact area : Gold 0.2μm min.
Lead area : Gold 0.03μm min.
Under plating : Nickel 2μm min.

4 Plating
Lead area : Gold 0.03μm min.
Under area : Nickel 0.2μm min.

NO.	MATERIAL	FINISH , REMARKS
1	PPS	BLACK, UL94V-0
2	PHOSPHOR BRONZE	3
3	STAINLESS STEEL	4

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	4 : 1	1	2	DIS-E-00002550	TA. TORIHARA	MN. KENJO	20190920

HIROSE ELECTRIC CO., LTD.

APPROVED	AO. SUZUKI	20061003
CHECKED	NF. MIYAZAKI	20061003
DESIGNED	HS. KIKUCHI	20061003
DRAWN	HS. KIKUCHI	20061003

DRAWING NO.	EDC3-045930-02
PART NO.	3260-8S1(55)
CODE NO.	CL232-0002-7-55

1/1