

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	② -40 °C TO +105 °C	STORAGE TEMPERATURE RANGE	③ -40 °C TO +60 °C	
	VOLTAGE		CURRENT		
			APPLICABLE WIRE	14 TO 50 sq	
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	QT AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X X
MARKING		CONFIRMED VISUALLY.			X X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△					
REMARK 1. THIS PRODUCT' s SPECIFICATIONS CONFORMS TO PS3C--1UP SPECIFICATIONS FOR USE IN COMBINATION WITH PS3C--1UP. ② THE OPERATION TEMPERATURE INCLUDES THE TEMPERATURE RISE BY CURRENT CARRYING. ③ STORAGE TEMPERATURE RANGE SHOWS STORAGE CONDITION FOR UNUSED PRODUCTS INCLUDING PACKING MATERIALS.FOLLOW THE OPERATING TEMPERATURE RANGE FOR STORAGE CONDITION AFTER MOUNTING. Unless otherwise specified, refer to JIS C 5402.			APPROVED	NM. NISHIMATSU	14. 07. 23
			CHECKED	NM. NISHIMATSU	14. 07. 23
			DESIGNED	WR. YAMADA	14. 07. 22
			DRAWN	WR. YAMADA	14. 07. 22
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-128556-00	
HRS	SPECIFICATION SHEET		PART NO.	PS3C-1UP-CVL	
	HIROSE ELECTRIC CO., LTD.		CODE NO	CL236-1066-0-00	△ 1/1