APPLICA	BLE STANI	DARD										
DATINO	OPERATING TEMPERATURI	RANGE	☐ -40 °C TO +10	5 °C		RAGE PERATU	RE RAN	GE	2	-40 °C T	O +60	°C
RATING	VOLTAGE		300 V AC,DC	)	CU	RRENT				5 A		
			SPECI	FICA	IOI	NS						
			TEST METHOD					REQU	IREMEN	TS	QT	AT
CONSTRUCTION GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.						
MARKING		CONFIRMED VISUALLY.				According to brawing.				X	X X	
		EOPER	ATION TEMPERATURE	INCLUDE	STH	ERISE						
	BY 2 STO FO FO	ORAGE R UNUS LLOW T	NT CARRYING. TEMPERATURE RANGE ED PRODUCTS INCLUD HE OPERATING TEMPE NAFTER MOUNTING.	ING PAC	KING	MATE	RIALS					
COUN	T DE	SCRIPTIO	ON OF REVISIONS	l	DESIG	NED			CHE	CKED	DA	TE
<u>A</u> REMARK							APPRO			T.W.W. 201		0.07
							CHEC			TAKAYASU NISHIMATSU	15.0 15.0	
							DESIG			SHIMOYAMA		6. 23
Unless otherwise specified, refe			fer to JIS C 5402.				DRA	WN		SHIMOYAMA	15.0	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				est	DRAWING N				ELO	C-128945-	-00-00	)
HRS	SF	SPECIFICATION SHEET			PART	NO.	NO. PS		2-1618SCFA-1000A			
	HIR	DSE EI	ECTRIC CO., LTD.	(	CODE		CL236-		6-1070-0-00		Ď	1/1

FORM HD0011-2-1