May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

## ② Attachment

JIS B 1188 : Cross recessed need screws with captive washer
M4×0.7×16













③ Electrode touched area for rack plating







Note 1. Refer to ETAD-E 2925 for the applicable components assembled with this product.
2. Swelling max 1.2mm dia. and 0.15mm height could appear on the surface due to die-casting, but it doesn't affect the performance.
③ The color of hatched area could be different due to the rack plating process, touching the electrodes to the specified area, but it doesn't affect the performance.

| NO. | MATERIAL | FINISH . REMARKS | NO. | MATERIAL | FINISH . REMARKS |
|---|---|---|---|---|---|
| 1 | ZDC2 | Surface plating : Nickel 2μm min<br>Under plating : Copper 7μm min | 2 | Steel | Surface plating : Nickel 2μm min<br>Under plating : Copper 3μm min |

| UNITS | SCALE | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|---|---|---|---|---|---|---|
| mm | 1 : 1 | 0 | | | | |

HIROSE ELECTRIC CO., LTD.

| | | | |
|---|---|---|---|
| APPROVED | NM. NISHIMATSU | 17.01.25 | DRAWING NO. EDC-126914-01-00 |
| CHECKED | NM. NISHIMATSU | 17.01.25 | PART NO. PQ50-20P-PC(01) |
| DESIGNED | MO. SHIMOYAMA | 17.01.25 | CODE NO. CL236-2000-8-01 |
| DRAWN | JY. IGA | 17.01.25 | 0 1/1 |

HRS DRAWING FOR REFERENCE