Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE

(2) Attachment

JIS B 1188 : Cross recessed need screws with captive washer
M4×0.7×16









(3) Electrode touched area for rack plating



Hatched bottom areas and the side wall up to 10 max. high from the bottom surface.



Note 1. Refer to ETAD-E 2925 for the applicable components assembled with this product.
2. Swelling max 1.2mm dia. and 0.15mm height could appear on the surface due to die-casting, but it doesn't affect the performance.
(3) The color of hatched area could be different due to the rack plating process, touching the electrodes to the specified area, but it doesn't affect the performance.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
1	ZDC2	Surface plating : Nickel 2μm min Under plating : Copper 7μm min	2	Steel	Surface plating : Nickel 2μm min Under plating : Copper 3μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	1 : 1	△0					

HIROSE ELECTRIC CO., LTD.

APPROVED	NM. NISHIMATSU	17. 01. 25	DRAWING NO.	EDC-126916-01-00
CHECKED	NM. NISHIMATSU	17. 01. 25	PART NO.	PQ50-20S-JC(01)
DESIGNED	MO. SHIMOYAMA	17. 01. 25	CODE NO.	CL236-2002-3-01 △0 1/1
DRAWN	JY. IGA	17. 01. 25		