APPLICAB	LE STANDARD							
RATING	OPERATING	_		DRAGE		_		
	TEMPERATURE RANGE		TE	MPERATURE 1	RANGE			
	VOLTAGE	_	100		-	_		
CURRENT — APPLICABLE CABLE —								
SPECIFICATIONS ITEM TEST METHOD REQUIREMENTS QT AT								
CONSTRUCTION		TEST METHOD	TEST METHOD		REQUIREMENTS			
CONSTRUCTION VICIALLY		TALLY AND DV NEAGUDING INCTDUNENT	AND DV MEACUDING INCTRINENT		T			
		IALLY AND BY MEASURING INSTRUMENT. TRMED VISUALLY.				ACCORDING TO DRAWING.		
MARKING CONFIRME		TIMED VISUALLI.	VISUALLI.		<u>I</u>			
COUN	T DESCE	RIPTION OF REVISIONS	DES	GNED		CHECKED	DATE	
<u>a</u>	. 52301	WI HELL ST KENISHS	520	0.1122		OHLOHED	5,112	
REMARK				ı	 APPROVE	D AO. SUZUKI	12. 03. 19	
I SEIVI II II S				ŀ	CHECKE		12. 03. 19	
				ŀ	DESIGNE		12. 03. 19	
				ŀ	DRAWN	P. EKSOURTYA	12. 03. 14	
Note QT:Qualification Test AT:Assurance Test X:Applicab			-	DRAWING		ELC4-12692	- I	
					G NU.		.0 00	
HS.	SPECIFICATION SHEET		PAR	T NO.		PQ50-SC-KY	<u>, </u>	
	HIROSE ELECTRIC CO., LTD.			E NO.	CL236-2009-2-00 🛕 1/1			