May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.











NOTE 1 LESS THAN φ4 mm IS PRESUMED CABLE SIZE.

2 CABLE SHALL BE OVERMOLDED WITH BUSHING TO FIX.
USE NON-MIGRATION RESIN FOR OVERMOLDING.

3 <PLATING>
CONTACT AREA:GOLD PLATED 0.2μm MIN.
LEAD AREA:GOLD PLATED FLASH.
UNDER PLATING:NICKEL PLATED 2μm MIN.

4 THE PRODUCT IS DELIVERED IN FOLLOWING CONDITIONS:
UNIT WITH REF ③ ASSEMBLED TO REF ④ AND ⑤, COVER WITH REF ① ASSEMBLED TO REF ⑧ AND ⑨, AND REF ② , ⑥ , ⑦ , ⑩ DISASSEMBLED.

5 CLAMP METAL FOR THIS PRODUCT IS SOLD SEPARATELY.

⚠1 6 REFER TO THE TECHNICAL SPECIFICATION(ETAP-E3217)FOR PACKING.

2 BUSHING, ASSEMBLY DIMENSIONS FOR REFERENCE



BUSHING DIMENSIONS FOR REFERENCE
(OVERMOLDING)



CABLE SHIELD IS CONNECTED BY CAULKING OF CLAMP METAL (COMMERCIAL ITEM) FITTING WITH CONNECTOR SHIELD REF ⑥.

HRS DRAWING FOR REFERENCE

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
5	COPPER ALLOY	3	10	STEEL	BLACK CHROMATE Cr3. (TAPPING SCREW)
4			9	STAINLESS STEEL	
3	POLYAMIDE	COLOR:BLACK UL94V-0	8	STAINLESS STEEL	
2	POLYCABONATE	COLOR:BLACK UL94V-0	7	STAINLESS STEEL	
1	POLYCABONATE	COLOR:BLACK UL94V-0	6	STAINLESS STEEL	

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	⚠1	1	DIS-E-00009892	KN. ICHIKAWA	KG. OKITA	20220624

HIROSE ELECTRIC CO., LTD.

APPROVED	NM. NISHIMATSU	20151027	DRAWING NO. EDC-123317-30-00
CHECKED	KN. ICHIKAWA	20151027	PART NO. ST40X-24S-CV(30)
DESIGNED	TS. ITO	20151027	CODE NO. CL0241-0004-3-30 ⚠1 1/1
DRAWN	AK. AKIYAMA	20151027	