

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO
Q1

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△											
APPLICABLE STANDARD											
RATING	OPERATING TEMPERATURE RANGE		—			STORAGE TEMPERATURE RANGE		—			
	VOLTAGE		—			OPERATING HUMIDITY RANGE		—			
	CURRENT		—			APPLICABLE CABLE		—			
SPECIFICATIONS											
ITEM		TEST METHOD				REQUIREMENTS				QT	AT
CONSTRUCTION											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				<input type="radio"/>	<input type="radio"/>
MARKING		CONFIRMED VISUALLY.				ACCORDING TO DRAWING.				<input type="radio"/>	<input type="radio"/>
REMARKS						DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
Unless otherwise specified, refer to JIS C 5402.						<i>F. Taniguchi</i> 02.06.03	<i>F. Taniguchi</i> 02.06.03	<i>Y. Enami</i> 02.6.3	<i>M. Matsuyaki</i> 02.6.3		
						Note QT:Qualification Test AT:Assurance Test ○:Applicable Test					
HS HIROSE ELECTRIC CO., LTD						SPECIFICATION SHEET			PART NO. ST40X-CM(4.0)		
CODE NO.(OLD) CL			DRAWING NO. ELC4 -123745			CODE NO. CL241-0014-7			1/1		