Q1

. 1	T			I		I		1 1	T					I		
•	COUNT	DESCRIPTION (	OF REVISION	ONS E	BY	CHKD	DATE	CC	UNT	DESCF	RIPTION C	F REVISIONS	BY	CHKD	DA	LE
À					_			<del>     </del>		<del></del>			<u> </u>			
$\triangle$								$\triangle$								-
AP	PLICA	BLE STAND TOPERATING	ARD						STOP	\CF						
RATING		TEMPERATURE RANGE		_ °C TO _ °C				;	STORAGE TEMPERATURE RANGE			_ °C TO _ °C				
		VOLTAGE					OPERATING HUMID		HUMIDIT	Y - % TO - %				6		
		CURRENT		<del>_</del>			APPLICABLE C		CABLE	φ5.8 +0/-0				ļ		
		CONTENT		SDECIE			$C\Lambda$	CATIONS			Ψ 3. δ +0/-0. Ζ					
	IT			т.	СТ		SPECIFICATION METHOD			<u> </u>	חבס	LUDENIEN	<u></u>		IOT.	A T
ITEM TEST					IVIE	METHOD			REQUIREMENTS					ועו	AT	
		XAMINATION \	VISUALLY	'AND B	Y ME	EASUF	RING INSTR	UMENT	. A	CCOR	DING TO	DRAWING.			To	0
	RKING	CONFIRMED VISUALI			<b>.</b> Y.				-					10	0	
<u> </u>															10	LO.
REMARKS				· · · · · ·	<del>.</del>			DBA	WN	DEC	IGNED	CHECKED	APPR	OVED	RELEA	SED
												Millohamuse 03.7.14	akir f	D.	RCLE#	νοcη
		erwise speci							1. 14	03.	1.14	03.7.NL	v3. 7	14		
Note	QT:Q	alification Test	AT:Assu	rance T	est	○:Ар	plicable Tes	t			DADT					
μ	S2					SPI	ECIFICA	TION	SH	EET	PART N		<i>(</i> =	۵۱		
	' <b>'</b>	HROSE ELEC	CTRIC CO	)., LTD	).					· = •	014	0 X - B S	(5)	. ø)		
	E NO.(OL	D)	DR	AWING N	NO.				COD	E NO.	·				1	1 /
(	CL		ı		<b>⊑</b> ∣ (	_ N _	124189		1		$\sim$	1 241-002	<b>5</b> 2			<i>/</i> . !