



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD		USB2.0 SPECIFICATION							
RATING	OPERATING TEMPERATURE RANGE	0 °C TO +50 °C			STORAGE TEMPERATURE RANGE	-20 °C TO +60 °C			
	VOLTAGE	—			OPERATING HUMIDITY RANGE	— % TO — %			
	CURRENT	—			APPLICABLE CABLE	USB CABLE (φ 3.8)			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×	×
MARKING		CONFIRMED VISUALLY.						×	×
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
					Y. Takeuchi 06.11.13	Y. Takeuchi 06.11.13	H. Kobayashi 06.11.13	 06.11.13	
Note QT:Qualification Test AT:Assurance Test ×:Applicable Test									
 HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET				PART NO. ZX40-SLDB			
CODE NO.(OLD) CL		DRAWING NO. ELC4-125859			CODE NO. CL242-0004-0			1/1	