

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE					
△					△									
△					△									
APPLICABLE STANDARD		USB2.0 SPECIFICATION AND MICRO-USB CABLES AND CONNECTORS SPECIFICATION												
RATING	OPERATING TEMPERATURE RANGE	-30 °C TO +85 °C			STORAGE TEMPERATURE RANGE	-30 °C TO +85 °C								
	VOLTAGE	—			OPERATING HUMIDITY RANGE	— % TO — %								
	CURRENT	—			APPLICABLE CABLE	—								
SPECIFICATIONS														
ITEM		TEST METHOD			REQUIREMENTS			QT	AT					
CONSTRUCTION														
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×	×					
MARKING		CONFIRMED VISUALLY.						×	×					
REMARKS HIROSE will not guarantee the performance on these specifications in case this product will be mated with the others which is not HIROSE's. Unless otherwise specified, refer to USB2.0 or EIA364.														
										DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
										<i>Td. Ando</i>	<i>Td. Ando</i>	<i>R. Koyama</i>	<i>[Signature]</i>	
										07.09.03	07.09.03	07.09.03	07.09.03	
Note QT:Qualification Test AT:Assurance Test ×:Applicable Test														
HRS HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET			PART NO. ZX40-A-SLDA									
CODE NO.(OLD)		DRAWING NO. ELC4-126049			CODE NO. CL242-0011-5			1/1						