APPLICA	BLE STAN	DARD									
	OPERATING TEMPERATURE RANGE OPERATING&STORAGE HUMIDTY RANGE VOLTAGE		-25°C TO +85°C		STORAGE TEMPERATURE RANGE			−25°C TO +60°C			
RATING			85%MAX		APPL	APPLICABLE CA		A	CABLE DIAMETER :	φ7.3~9.3	
	CURF	RENT									
			SPEC	IFIC/	OITA	NS					
ITEM		TEST METHOD				REQUIREMENTS					AT
CONSTRUCTION GENERAL EXAMINATION		VISUALLY		ACCORDING TO DRAWING.					X		
MARKING		CONFIRMED VISUALLY.								X	
											1
COUNT DES		SCRIPTION OF REVISIONS			DESIGNED			CHECKED		D/	L ATE
1		DIS-E-00003216			KN. ICH				TU. TANIGUCHI	_	01019
REMARK							APPRO	VED	KN. ICHIKAWA	201	00405
			PLIES TO DH40-37	CHECKE		KED	KN. ICHIKAWA	201	00405		
DH3 * B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to IEC 60512.						DESIG		NED	MO. SHIMOYAMA	201	00405
								۷N	TM. ONO	2010040	
						RAWING NO.			ELC-126588-13-13		
ЖS	SI	PECIFIC	CATION SHEET	Т		PART NO.		DH-37-CV1B (13)			
11/2	HIROSE ELECTRIC CO., LTD.				CODE NO.		С	CL244-0011-8-13			1/1