| APPLICA | BLE STAN | DARD | | | | | | | | | |
|---|---|----------------|---------------------------------------|------------------------------|------------------------|--|-----------------|-------------------------|----------------|-------|--|
| OPERATING TEMPERATURE RANGE | | | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | STORAGE TEMPERATURI | = RANGE | | −25°C TO +60° | −25°C TO +60°C | | |
| RATING | OPERATING&STORAGE HUMIDTY RANGE | | 85%MAX | | APPLICABL | ICABLE CABLE | | Δ CABLE DIAMETER: φ6.4~ | | | |
| | CU | IRRENT | | | VOLTAGE | | | | | | |
| | • | | | | | | • | | | | |
| | | | SPEC | IFIC/ | ATIONS | | | | | | |
| | EM | | TEST METHOD | | | REQUIREMENTS QT AT | | | | | |
| CONSTRUCTION GENERAL EXAMINATION VISUALLY AND BY | | | Y MEASURING INSTRUMENT. ACC | | | ORDING TO DRAWING. X X | | | | | |
| MARKING | | CONFIRMED VISI | | _ | | | | ^ X | | | |
| WATCH | | | | | | | | | X | ^ | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| COUN | T DE | SCRIPTION OF I | | | | | | CHECKED | | ΛTE | |
| 1 REMARK | 1 DIS-E-00014810 | | | | KIM JAEHYEON | | | KG. OKITA | 20230928 | | |
| | RODUCT SH | HALL BE MATE | D WITH DH3 * B-2 | WITH DH3 * B-27S, IT APPLIES | | | VED | AO. SUZUKI | 20100407 | | |
| | | | ANICAL, ENVIRON | AL | CHECK | | AH. KODAMA | | | | |
| | ACTERISTIC | | | | | DESIGN | | MO. SHIMOYAMA | - | 00407 | |
| Unless otherwise specified, refer to IEC 60512. | | | | | DRAWN | | | TM. 0N0 20100407 | | | |
| Note QT:Q | ote QT:Qualification Test AT:Assurance Test X:Applicable Test D | | | | | WING NO. ELC4-126627-13 O. DH-27-CT1B (13) | | | | | |
| H3C | SPECIFICATION SHEET | | | | | | DH-27-CT1B (13) | | | | |
| 11. | HIROSE ELECTRIC CO., LTD. | | | | CODE NO | CI | 1/1 | | | 1/1 | |