




Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
			APPLICABLE CABLE	CABLE DIAMETER : $\phi 6.3 \pm 0.5$	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
					
REMARK Unless otherwise specified, refer to JIS C 5402.			APPROVED	A0. SUZUKI	09. 04. 16
			CHECKED	MO. SHIMOYAMA	09. 04. 16
			DESIGNED	TS. ITO	09. 04. 14
			DRAWN	TS. ITO	09. 04. 14
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126657-00
	SPECIFICATION SHEET		PART NO.	DH-17-CMB (6. 3)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0031-5-00	 1/1