

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	VOLTAGE		APPLICABLE CABLE	△ CABLE DIAMETER : φ6.4~7.8	
	CURRENT				
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			X	X
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△	1	DIS-E-00014810	KIM JAEHYEON	KG. OKITA	20230928
REMARK			APPROVED	AO. SUZUKI	20090511
THIS PRODUCT SHALL BE MATED WITH DH30B-27S, IT APPLIES TO DH30B-27S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.  Unless otherwise specified, refer to IEC 60512.			CHECKED	KN. ICHIKAWA	20090511
			DESIGNED	MO. SHIMOYAMA	20090511
			DRAWN	MO. SHIMOYAMA	20090511
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test		
<b>HRS</b>	SPECIFICATION SHEET		PART NO.	DH-27-CT2B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0244-0048-8-00	△ 1/1