APPLICA	BLE STAN	DARD							
RATING TEMPERATURE RANG		RE RANGE	-40°C TO +70°	C I	STORAGE TEMPERATU	RE RANGE	_		
			SPECI	FICAT	IONS	·			
	EM		TEST METHOD			REQU	JIREMENTS	QT	АТ
	RUCTION	Tyron and 197	AND DV MEAGUDING INCTOL	MACNIT	LAGGORI		MINIO	1 1/2	
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCOR	ACCORDING TO DRAWING.		X	X
MARKING		CONFIRMED VISUALLY.						Х	Х
ENVIROI	NMENTAL	CHARA	ACTERISTICS		<u> </u>			<u> </u>	
DAMP HEAT (STEADY STATE)		EXPOSED AT +40 °C, 90~95 % 96 h \(\Lambda\)			1	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		×	_
RAPID CHANGE OF TEMPERATURE		TEMPERATURE $-55\pm3 \rightarrow 5 \text{ TO } 35 \rightarrow +85\pm2 \rightarrow 5 \text{ TO } 35 ^{\circ}\text{C}$ TIME $30 \text{ TO } 35 \rightarrow 5 \text{ MAX.} \rightarrow 30 \text{ TO } 35 \rightarrow 5 \text{ MAX.}$ mir UNDER 5 CYCLES.						Х	_
COUN	T D	ESCRIPTION	ON OF REVISIONS	DI	ESIGNED		CHECKED	DA	TE
<u> </u>			-E-003672		TS. 1T0		TA. ASO	11.0	
REMARK	•		1			APPROVED		09.0	
						CHECKED	NF.MIYAZAKI	09.0	
1-1		. '6' !	itiad refer to 110 0 5400			DESIGNED	HS. KTKUCHT	09.0	
Unless otherwise specified, re						DRAWN	HS. KIKUCHI	09.0	1. 13
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				st	DRAWIN	G NO.	ELC4-12616	9-00	
HS	SI	PECIFI	CIFICATION SHEET		ART NO.	LX40-20BS (5. 0)			
	HIR	OSE EL	ECTRIC CO., LTD.	c	DDE NO.	CL245-0022-0-00 🛕 1			1/1