



Applicable standard					
Rating	Operating temperature range	-55 °C to +85 °C (95 %RH Max.)	Storage temperature range	-55 °C to +85 °C (95 %RH Max.)	
	Power	-- W	Characteristic impedance	50 Ω(0 to 10 GHz)	
	Peculiarity	----	Applicable cable	----	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
General examination	Visually and by measuring instrument.		According to drawing.	X	X
Marking	Confirmed visually.			X	X
ELECTRICAL CHARACTERISTICS					
Contact resistance	100 mA Max.(DC or 1000 Hz)		Center contact 6 mΩ Max.	X	X
			Outer contact 6 mΩ Max.	X	X
Insulation resistance	500 V DC.		1000 MΩ min.	X	X
Withstanding voltage	1500 V AC for 1 min. current leakage 2 mA Max.		No flashover or breakdown.	X	X
Voltage standing wave ratio	Frequency 0 to 10 GHz.		VSWR 1.2 Max.	X	-
	Frequency 0 to 10 GHz.		0.2 dB Max.	X	-
MECHANICAL CHARACTERISTICS					
Contact insertion and extraction forces	φ by steel gauge.		Insertion force ---- N Max.	-	-
			Extraction force ---- N Min.	-	-
Insertion and extraction forces	Measured by applicable connector.		Insertion force ---- N Max.	-	-
			Extraction force ---- N Max.	-	-
Mechanical operation	1000 times insertion and extractions.		1)Contact resistance: Center contact 20 mΩ Max. Outer contact 20 mΩ Max. 2)No damage, crack and looseness of parts.	X	-
Vibration	Frequency 10 to 500 Hz single amplitude 0.75 mm, 98 m/s ² at 10 cycles for 3 directions.		1)No electrical discontinuity of 1 μs. 2)No damage, crack and looseness of parts.	X	-
Shock	490 m/s ² directions of pulse 11 ms at 3 times for 3 directions.			X	-
Cable clamp strength (Against cable pull)	Using a pulling tester, pull the cable axially at a rate of -- mm/min. and record the strength at which the cable or connector breaks.		---- N Min.	-	-
ENVIRONMENTAL CHARACTERISTICS					
Damp heat	Exposed at +25 to +65 °C, 90 to 96 % total 10 cycles.(240 h)		1)Insulation resistance: 100 MΩ Min. (at high humidity) 2) Insulation resistance: 1000 MΩ Min. (at dry) 3)No damage, crack and looseness of parts.	X	-
Rapid change of temperature	Temperature -55 → - → +85 → - °C Time 30 → 3 → 30 → 3 min. Under 5 cycles.		No damage, crack and looseness of parts.	X	-
Corrosion salt mist	Exposed in 5 % salt water spray for 48 h.		VSWR 1.2 Max.	X	-
	Count	Description of revisions	Designed	Checked	Date
 Remark				Approved	TO.KATAYAMA 20200526
				Checked	TO.KATAYAMA 20200526
				Designed	TM.YOSHIDA 20200526
				Drawn	TM.YOSHIDA 20200526
Unless otherwise specified, refer to IEC 60512.					
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test		Drawing No.	ELC-000470-40-40	
	SPECIFICATION SHEET		Part No.	UG-57B/U(40)	
	HIROSE ELECTRIC CO., LTD.		Code No.	CL301-0018-7-40	