May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Applicable standard				
Rating	Operating temperature range	-40 °C to +90 °C(90 %RH Max.)	Storage temperature range	-40 °C to +90 °C(90 %RH Max.)
	Power	-- W	Characteristic impedance	50 Ω(0 to 6 GHz)
	Peculiarity	----	Applicable cable	0.50 Dia. coaxial cable.

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
General examination	Visually and by measuring instrument.	According to drawing.	X	X
ELECTRICAL CHARACTERISTICS				
Insulation resistance	100 V DC.	500 MΩ Min.	X	X
Withstanding voltage	200 V AC for 1 min. current leakage 2 mA Max.	No breakdown. △1	X	X
Voltage standing wave ratio 1	Frequency 0 to 3 GHz. Frequency 3 to 6 GHz.	VSWR 1.3 Max. VSWR 1.4 Max.	X	—
MECHANICAL CHARACTERISTICS				
Cable clamp strength (Against cable pull)	Using a pulling tester, pull the cable axially at a rate of 10 mm/min. and record the strength at which the cable or connector breaks.	7 N Min.	X	—

	Count	Description of revisions	Designed	Checked	Date
△1	2	DIS-D-00011757	MS. MATSUMOTO	MT. KANEKO	20220510

Remark HALOGEN FREE

Notes 1 VSWR is measured with SMA conversion adapters attached to both ends of the applicable cable assembled.

2. "L" at the end of the product name indicates the cable length (unit:mm).

3. Specifications are subject to change without notice.

Unless otherwise specified, refer to IEC 60512. △1

Approved	NK.NINOMIYA	20160728
Checked	MT.KANEKO	20160728
Designed	MS.MATSUMOTO	20160728
Drawn	MS.MATSUMOTO	20160728

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

HRS	SPECIFICATION SHEET	Drawing No.		
		Part No.	WFL2-2LPHF6-032**TS-A-L	
	HIROSE ELECTRIC CO., LTD.	Code No.		△1 1/1

FORM HD0011-2-1