Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△						△					. .
△						△					. .



RECOMMENDED PC BOARD
PATTERN DRAWING (5 : 1)







HRS DRAWING FOR REFERENCE

NOTE 1. THE QUANTITY OF E.FL-LR-SMT(01) IS 100 CONNECTORS PER PACK.

2 ENGAGEMENT SIDE SHOULD BE PLACED IN 0.3mm MAX. FROM THE EDGE OF PCB WHEN MOUNTED ON PCB.

3. LEAD CO-PLANARITY TO BE 0.1 MAX.

2 MOUNTED CONNECTOR ON PCB



NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
2	LCP	(BLACK) UL94V-0			
1	PHOSPHOR BRONZE	SILVER PLATING	3	BRASS	GOLD PLATING

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	Y. Sugiyama	T. Katayama	K. Shimizu	O. Mitani	
RoHS COMPLIANT	'06.06.02	'06.06.02	06.06.05	'06.06.03	

SCALE 10 : 1	DRAWING NO. EDC4-131127-01	PART NO. E.FL-LR-SMT(01)	
UNITS mm	HRS HIROSE ELECTRIC CO.,LTD.	CODE NO. CL331-0422-4-01	1/1

TO
RF

FORM NO.228