

Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .

REEL DIMENSIONS(Free)




ENBOSSED TAPING DRAWING(4:1)






HRS DRAWING FOR REFERENCE

[2] MOUNTED CONNECTOR ON PCB (8:1)



RECOMMONDED PC BOARD PATTERN DRAWING (5:1)



NOTE 1. THE QUANTITY OF E.FL-LR-SMT(10) IS 2500 CONNECTORS PER REEL.

[2] ENGAGEMENT SIDE SHOULD BE PLACED IN 0.3mm MAX. FROM THE EDGE OF PCB WHEN MOUNTED ON PCB.

3. LEAD CO-PLANARITY TO BE 0.1 MAX.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
2	LCP	(BLACK)UL94V-0	3	BRASS	GOLD PLATED 0.2μmMIN
1	PHOSPHOR BRONZE	SILVER PLATING 2μm MIN			OVER NICKEL PLATED 1.27μm MIN

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	J.Akuwa 97.2.10	N.Ninomiya 97.2.10	S.Mitani 97.2.10	Y.Kobayashi '97.2.10	

SCALE	DRAWING NO.	PART NO.
10:1	EDC3-131127-10	E.FL-LR-SMT(10)
UNITS mm	HRS HIROSE ELECTRIC CO.,LTD.	CODE NO. CL331-0422-4-10 1/1

FORM No.233

TO
RF