
Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




NOTES 1 PLEASE HOLD THE FLANGE WITH A SPANNER WHEN MATING THE CONNECTOR TO AVOID ANY TORQUE ACTING ON THE PCB.


2 0-80UNF-2B SCREWS TIGHTENING TORQUE SHOULD BE 0.09N・m.
PLEASE TIGHTEN THE SCREWS EVENLY WHEN MOUNTING THE CONNECTORS TO ENSURE STABLE ELECTRICAL CONTACT.


3 PLEASE USE ATTACHED SCREWS AND WASHERS FOR MOUNTING.
ATTACHED SCREWS AND WASHERS ARE APPLICABLE ON PCB WITH THICKNESS T=2.4 TO 4.25mm.


4 THE SOLDER MASK PROHIBITED AREA IS INDICATED.


⚠1 5. THIS PRODUCT IS A SOLDERLESS CONNECTOR FOR PROTOTYPE EVALUATION OF HIGH SPEED TRANSMISSION BOARDS.
IT IS NOT RECOMMENDED FOR USE IN ACTUAL COMMERCIAL EQUIPMENT.























NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	BERYLLIUM COPPER	GOLD PLATING	6	STAINLESS STEEL	SPRING WASHER
2	PTFE		5	STEEL	0-80UNF-2A SCREW
1	STAINLESS STEEL	PASSIVATE	4	STAINLESS STEEL	GOLD PLATING

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm/inch	5 : 1	⚠1	1	DIS-D-00016641	TS. KANEKO	TS. NAKAGAWA	20230824

HIROSE ELECTRIC CO., LTD.

APPROVED	TS. NOBE	20180425	DRAWING NO. EDC-381620-11-00
CHECKED	MH. OGUSU	20180425	PART NO. H2.4-R-SR2-1(11)
DESIGNED	AH. MARUYAMA	20180425	CODE NO. CL0338-0607-0-11 ⚠1 1/1
DRAWN	EDWIN TANG	20180425	

HRS DRAWING FOR REFERENCE