

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT		DESCRIPTION OF REVISIONS		BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS		BY	CHKD	DATE
△							△					
△							△					
△							△					







FIGURE 1(2:1)



NOTE 1.Use this product with MS-156(CL358-0167-4).
2.Mating angle must be less than ±2 degree.(refer to figure 1)

5	BERYLLIUM COPPER	GOLD	10	STAINLESS STEEL	PASSIVATE
4	PHOSPHOR BRONZE	GOLD	9	PTFE	
3	PHOSPHOR BRONZE	NICKEL	8	PTFE	
2	PHOSPHOR BRONZE	GOLD	7	PTFE	
1	PHOSPHOR BRONZE	NICKEL	6	STAINLESS STEEL	GOLD

CODE NO. (OLD)		DRAWN		DESIGNED		CHECKED		APPROVED		RELEASED	
		K. Hida		K. Hida		K. Hida		Y. Higuchi			
		02.6.26		02.6.26		02.6.26		02.6.27			
DRAWING NO.		EDC3-180280		PART NO.		MS-156-HRMJ-2					
SCALE		4 : 1		CODE NO.		CL358-0170-2					
UNITS		mm		HIROSE ELECTRIC CO., LTD							

TO	
RFD	