Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE









Notes 1 Contact No. (5, 10, 15, 20, 25, 30) are shown.
2 A polarizing key inserted between the following contact positions. (5 to 6), (10 to 11), (15 to 16), (20 to 21), (25 to 26).
3 The dimensions in parentheses are for reference.

Recommended PC board hole pattern (t=1.6±0.1)



NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	PHOSPHOR BRONZE	(Contact area)Ni2.5μm+Au0.05μm (Mounting area)Ni2.5μm+Sn2μm	3	PHOSPHOR BRONZE	(Contact area)Ni2.5μm+Au0.05μm (Mounting area)Ni2.5μm+Sn2μm
1	PBT	BLACK UL94V-0			

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	0				

HIROSE ELECTRIC CO., LTD.

APPROVED	HT. YAMAGUCHI	18. 06. 25	DRAWING NO. EDC-018063-70-01
CHECKED	HT. YAMAGUCHI	18. 06. 25	PART NO. CR22-60D-2.54DSA(70)
DESIGNED	TY. EDAGAWA	18. 06. 25	
DRAWN	MK. OOKI	18. 06. 21	CODE NO. CL522-0028-8-70 0 1/1