May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE









Notes 1 Contact No. (5, 10, 15, 20, 25, 30) are shown.
2 A polarizing key inserted between the following contact positions. (5 to 6), (10 to 11), (15 to 16), (20 to 21), (25 to 26), (30 to 31).
3 The dimensions in parentheses are for reference.

Recommended PC board hole pattern (t=1.6±0.1)



NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	PHOSPHOR BRONZE	(Contact area)Ni2.5μm+Au0.05μm (Mounting area)Ni2.5μm+Sn2μm	3	PHOSPHOR BRONZE	(Contact area)Ni2.5μm+Au0.05μm (Mounting area)Ni2.5μm+Sn2μm
1	PBT	BLACK UL94V-0			

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	0				

HRS HIROSE ELECTRIC CO., LTD.

APPROVED	HT. YAMAGUCHI	18. 06. 25
CHECKED	HT. YAMAGUCHI	18. 06. 25
DESIGNED	TY. EDAGAWA	18. 06. 25
DRAWN	MK. OOKI	18. 06. 21

DRAWING NO.	EDC-018067-70-01
PART NO.	CR22-68D-2.54DSA(70)
CODE NO.	CL522-0030-0-70

0 1/1