



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.












RECOMMENDED METAL MASK (10:1)



RECOMMENDED PATTERN (10:1)




RECOMMENDED THICKNESS OF
SOLDER PASTE : 120 μm



HRS DRAWING FOR REFERENCE

NOTES 1 : LEAD CO-PLANARITY INCLUDING REINFORCED METAL FITTINGS SHALL BE 0.08 mm MAX.
2 : IF THERE IS PATTERN ON ▨ PART, THERE IS A POSSIBILITY
THAT IT WILL MAKE CONTACT WITH THE LEADS.
3 : REINFORCED METAL FITTINGS AS FOLLOWS.



NO.	MATERIAL	FINISH , REMARKS
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATED 0.2μm min LEAD AREA:GOLD PLATED 0.015μm min OTHERS(UNDER PLATING):NICKEL PLATED 2μm min
1	POLYAMIDE	UL94V-0, BLACK

NO.	MATERIAL	FINISH , REMARKS
6	PS	BLACK(PLASTIC REEL)
5	POLYESTER	CLEAR(COVER TAPE)
4	PS	CLEAR(EMBOSSED CARRIER TAPE)
3	BRASS	TIN PLATED 2μm min (UNDER PLATING):NICKEL 1μm min


UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	0				


HRS HIROSE ELECTRIC CO., LTD.

APPROVED	WR. FUKUCHI	20200512	DRAWING NO. EDC-389267-51-01
CHECED	TS. MIYAZAKI	20200512	PART NO. DF12NB-50DS-0.5V(51)
DESIGNED	KT. KUSAKA	20200512	
DRAWN	KT. KUSAKA	20200512	CODE NO. CL537-0291-0-51


0 1/2

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.






STYLE AND DIMENSION OF REEL



DIRECTION OF UNREELING

C-C



HRS DRAWING FOR REFERENCE

NOTES 4. 1 REEL:1000 CONNECTORS.
5. AT THE BEGINNING OF THE REEL, 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.
6. PEEL FORCE REFERS TO JIS C 0806.

DRAWING NO.	EDC-389267-51-01
PART NO.	DF12NB-50DS-0.5V(51)
CODE NO.	CL537-0291-0-51

△0 2/2