




Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
Mar.1.2024
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

















RECOMMENDED THICKNESS OF
SOLDER PASTE : 120 μm

HRS DRAWING FOR REFERENCE





NOTES 1 : LEAD CO-PLANARITY INCLUDING REINFORCED METAL FITTINGS SHALL BE 0.08 mm MAX.
2 : IF THERE IS PATTERN ON ▨ PART, THERE IS A POSSIBILITY THAT IT WILL MAKE CONTACT WITH THE LEADS.
3 : REINFORCED METAL FITTINGS AS FOLLOWS.



NO.	MATERIAL	FINISH , REMARKS
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATED 0.2μm min LEAD AREA:GOLD PLATED 0.015μm OTHERS(UNDER PLATING):NICKEL PLATED 2μm min
1	POLYAMIDE	UL94V-0, BLACK


NO.	MATERIAL	FINISH , REMARKS
6	PS	BLACK (PLASTIC REEL)
5	POLYESTER	CLEAR (COVER TAPE)
4	PS	CLEAR (EMBOSSED CARRIER TAPE)
3	BRASS	TIN PLATED 2μm min (UNDER PLATING):NICKEL 1μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△0					

HIROSE ELECTRIC CO., LTD.


APPROVED	WR. FUKUCHI	20200512	DRAWING NO. EDC-389325-51-01
CHECED	TS. MIYAZAKI	20200512	PART NO. DF12NB(5.0)-50DP-0.5V(51)
DESIGNED	KT. KUSAKA	20200512	CODE NO. CL537-0881-0-51
DRAWN	KT. KUSAKA	20200512	△0 1/2

Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demands high reliability, kindly contact our sales window correspondents.





STYLE AND DIMENSION OF REEL(FREE)



DIRECTION OF UNREELING

C–C

HRS DRAWING FOR REFERENCE

NOTES 4. 1 REEL:1000 CONNECTORS.
5. AT THE BEGINNING OF THE REEL, 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.
6. PEEL FORCE REFERS TO JIS C 0806.

DRAWING NO.	EDC-389325-51-01
PART NO.	DF12NB(5.0)-50DP-0.5V(51)
CODE NO.	CL537-0881-0-51

△0 2/2