

Nov.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△					
△					△					
<b>APPLICABLE STANDARD</b>										
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-30 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10 °C To + 60 °C				
	VOLTAGE				APPLICABLE CONNECTORS					
	CURRENT				OPERATING HUMIDITY RANGE	UL1007, AWG24				
<b>SPECIFICATIONS</b>										
<b>ITEM</b>	<b>TEST METHOD</b>				<b>REQUIREMENTS</b>				<b>QT</b>	<b>AT</b>
<b>CONSTRUCTION</b>										
<b>GENERAL EXAMINATION</b>		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.				×	×
<b>MARKING</b>		CONFIRMED VISUALLY.							×	×
<b>REMARKS</b>					<b>DRAWN</b>	<b>DESIGNED</b>	<b>CHECKED</b>	<b>APPROVED</b>	<b>RELEASED</b>	
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT					Y.NAGASHIMA	<i>Y. Inoue</i>	<i>Miyazaki</i>	<i>K. Katayama</i>		
Unless otherwise specified, refer to MIL-STD-1344.					'00.11.10	'00.11.10	'00.11.13	'00.11.14		
Note QT: Qualification Test AT: Assurance Test ×:Applicable Test										
<b>HRS HIROSE ELECTRIC CO., LTD.</b>					<b>SPECIFICATION SHEET</b>			<b>PART NO.</b>		
					DF1-*A1.33					
CODE NO.(OLD)			DRAWING NO.			PEART NO				
CL			ELC4-162341			CL541				
						1/1				

TO

