

Jun.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C(NOTE 1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C(NOTE 3)	
	OPERATING HUMIDITY RANGE	40% TO 80%(NOTE 2)	STORAGE HUMIDITY RANGE	40% TO 70%(NOTE 3)	
	VOLTAGE	250 V AC	APPLICABLE CONNECTORS	DF1B- * ES-2.5RC(#)	
	CURRENT	AWG20 TO 24 : 3 A AWG26 : 2 A AWG28 : 1 A AWG30 : 0.5 A	UL · CSA RATING	VOLTAGE CURRENT	AC 30V AWG20-22 : 3A AWG24-28 : 1A AWG30 : 0.5A
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
ELECTRIC CHARACTERISTICS					
INSULATION RESISTANCE	500 V DC.	1000 MΩ MIN.	X	—	
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—	
MECHANICAL CHARACTERISTICS					
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—	
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—	
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.	① INSULATION RESISTANCE: 1000 MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→ 5 TO 35→85→ 5 TO 35°C TIME 30→10 TO 15→30→10 TO 15 min UNDER 5 CYCLES.	① INSULATION RESISTANCE:1000 MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—	
REMARKS					
NOTE1:INCLUDING THE TEMPERATURE RISING BY CURRENT.					
NOTE2:NO CONDENSING.					
NOTE3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD AFTER PCBBOARD , OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERM STORAGE DURING TRANSPORTATION.					
Unless otherwise specified, refer to JIS C 5402.					
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△	1	DIS-H-005021	HT. SATO	HK. UMEHARA	10. 07. 22
△ format change.			APPROVED	KJ. KATAYOSE	05. 01. 05
			CHECKED	TY. OMA	05. 01. 05
			DESIGNED	TS. KUMAZAWA	05. 01. 05
			DRAWN	TS. KUMAZAWA	05. 01. 05
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-160055-01	
HRS	SPECIFICATION SHEET		PART NO.	DF1B-*EP-2. 5RC	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL541	△ 1/1