

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△				.	
△					△				.	
△					△				.	

Technical drawing of a connector with dimensions and cross-sections A-A and B-B. Dimensions include 14±0.25, 9.5±0.15, 6.1±0.25, 2.5±0.2, 1.95±0.15, 1.75±0.15, 0.975±0.15, 1.6±0.2, 1.4±0.2, 5±0.15, 1.4, 1.6, 1.8, and 2.45. Cross-sections A-A and B-B show internal details. A 'HRS mark' is indicated on the side view. A large diagonal watermark 'HRS DRAWING FOR REFERENCE' is overlaid on the drawing.

NOTES 1. APPLICABLE CABLE : AWG24 TO 28  
2. GOLD PLATE AREA

1	PHOSPHOR BRONZE	CONTACT: GOLD PLATING 0.2 μm OTHER: NICKEL PLATING 1 μm
NO.	MATERIAL	FINISH, REMARKS

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	Y. INOUE	Y. Inoue	T. Miyazaki	K. Katayama	
	00.09.18	00.9.18	00.9.18	00.9.18	

DRAWING NO.	PART NO.
EDC4-080532	DF1B-2428SCFA

UNITS	CODE NO.
mm	CL541-0680-3

HIROSE ELECTRIC CO., LTD.

1

2

3

4

TO

F

1

2

3

4

FORM NO. 22B

NC