



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.









Recommend metal mask
Thickness : 0.15 to 0.2mm
Opening ratio : 100%





1 Configuration of 2 to 6 position



Part No.	Code No.	A	B	C	D	E
DF3E- 2P-2H(24)	CL543-0343-0-24	4.6	2.0	8.5	4.8	8.74
DF3E- 3P-2H(24)	CL543-0344-0-24	6.6	4.0	10.5	6.8	10.74
DF3E- 4P-2H(24)	CL543-0345-0-24	8.6	6.0	12.5	8.8	12.74
DF3E- 5P-2H(24)	CL543-0346-0-24	10.6	8.0	14.5	10.8	14.74
DF3E- 6P-2H(24)	CL543-0347-0-24	12.6	10.0	16.5	12.8	16.74
DF3E- 7P-2H(24)	CL543-0348-0-24	14.6	12.0	18.5	14.8	18.74
DF3E- 8P-2H(24)	—	16.6	14.0	20.5	16.8	20.74
DF3E- 9P-2H(24)	—	18.6	16.0	22.5	18.8	22.74
DF3E-10P-2H(24)	CL543-0351-0-24	20.6	18.0	24.5	20.8	24.74
DF3E-11P-2H(24)	—	22.6	20.0	26.5	22.8	26.74
DF3E-12P-2H(24)	—	24.6	22.0	28.5	24.8	28.74
DF3E-13P-2H(24)	—	26.6	24.0	30.5	26.8	30.74
DF3E-14P-2H(24)	CL543-0355-0-24	28.6	26.0	32.5	28.8	32.74
DF3E-15P-2H(24)	—	30.6	28.0	34.5	30.8	34.74

Notes 1 It shows configuration of 2 to 6 position.
2. Lead co-planarity include reinforced metal fittings shall be 0.1mm MAX.

HRS DRAWING FOR REFERENCE

NO.	MATERIAL	FINISH , REMARKS
5	ELASTOMER 1	Gray
4	R.PVC 1	Electrostatic protection, Clear
3	Brass	Surface:Tin plated 1μm MIN (Under plating)Nickel plated 1μm MIN
2	Brass	Surface:Tin plated 1μm MIN (Under plating)Copper plated 0.5μm MIN
1	Polyamide	Natural(Beige), UL94V-0


UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	1	2	DIS-H-00005648	SN. MIWA	SZ. ONO	20200120

HIROSE ELECTRIC CO., LTD.


APPROVED	HS. OKAWA	20180216
CHECKED	TS. FUKUSHIMA	20180216
DESIGNED	TS. KUMAZAWA	20180216
DRAWN	MK. INOUE	20180216

DRAWING NO. EDC-369406-24-00
PART NO. DF3E-*P-2H(24)
CODE NO. CL543- 1 1/2

Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



G−G (10 : 1)



Notes 3. Number of connecters per a magazine case shall be in accordance with the list.
4. These connectors shall be on saled in accordance with the multiple quantity on the list.

Part No.	Code No.	Number of connectors
DF3E- 2P-2H(24)	CL543-0343-0-24	41
DF3E- 3P-2H(24)	CL543-0344-0-24	34
DF3E- 4P-2H(24)	CL543-0345-0-24	30
DF3E- 5P-2H(24)	CL543-0346-0-24	26
DF3E- 6P-2H(24)	CL543-0347-0-24	23
DF3E- 7P-2H(24)	CL543-0348-0-24	21
DF3E- 8P-2H(24)	—	19
DF3E- 9P-2H(24)	—	18
DF3E-10P-2H(24)	CL543-0351-0-24	17
DF3E-11P-2H(24)	—	15
DF3E-12P-2H(24)	—	14
DF3E-13P-2H(24)	—	14
DF3E-14P-2H(24)	CL543-0355-0-24	13
DF3E-15P-2H(24)	—	12

HRS DRAWING FOR REFERENCE

HRS	DRAWING NO.	EDC-369406-24-00
	PART NO.	DF3E-*P-2H(24)
	CODE NO.	CL543- △1 2/2