Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

7 MATING FIGURE (PANEL MOUNTED)







3 4 RECOMMENDED PANEL CUTOUT DIMENSION





1 FIGURE-1 CONTACT No. MARKING (10:1)



NOTE.
1. 1 MARKINGS AT THE INDICATED POSITIONS ARE CONTACT NO. MARKING. AND SHAPES ARE SHOWN IN FIGURE-1.
2. 2 PLEASE USE THE NON-RADIUS SIDE FOR THE PANEL HOOKING AREA.
3. 3 APPLICABLE PANEL THICKNESSING IS 2.3 TO 0.5mm.
4. 4 CONSULT HIROSE FOR THE OTHER PANEL CUTOUT DESIGNS THAN THE RECOMMENDED ONE.
5. PER PACK : 100 PIECES.
6. THE DIMENSIONS IN PARENTHESIS ARE FOR REFERENCE.
7. 7 THIS FIGURE SHOWS THE MATED CONDITION WITH DF62B-13S-2.2C.

NO.	MATERIAL	FINISH , REMARKS
1	PBT	UL94V-0(RED)

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	4 : 1	0					

HIROSE ELECTRIC CO., LTD.

APPROVED	SJ. OKAMURA	20220207
CHECED	SZ. ONO	20220204
DESIGNED	SS. YAMASAKI	20220204
DRAWN	SS. YAMASAKI	20220204

DRAWING NO.	EDC-349141-18-00
PART NO.	DF62P-13EP-2.2C(18)
CODE NO.	CL0544-0549-8-18

0 1/1

FORM HC0011-5-7_AN

HRS DRAWING FOR REFERENCE