

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE	
△						△						
△						△						
APPLICABLE STANDARD												
RATING	ELECTRIC SOURCE	PHASE	AC-DC	V	Hz	WEIGHT	1kg					
	DISSIPATION POWER					APPLICABEL CONNECTOR	DF60-1012SCA	680-3022-7				
	AIR SOURCE						DF60-1012PCA	680-3049-3				
	AIR CONSUMPTION					APPLICABLE CABLE						
	OPERATING TEMPERATURE LIMIT	°C~°C				APPLICABLE EQUIPMENT						
	SPECIFICATIONS											
CONSTITUTION	ITEM	TEST METHOD				REQUIREMENTS		QT	AT			
	APPEARANCE, STRUCTURE AND FINISH	Visually and by measuring instrument.				According to drawing.		○	○			
	MARKING	Confirmed visually.				According to drawing.		○	○			
REMARKS												
						DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
						14.8.21 M.SATO	14.8.21 M.SATO	14.8.25 T.Ito	14.8.25 T.Ito			
Unless otherwise specified, refer to												
Note QT:Qualification Test AT:Assurance Test X:Applicable Test												
HRS HIROSE ELECTRIC CO.,LTD.						SPECIFICATION SHEET			PART NO. HT306/DF60-1012			
CODE NO. (OLD)		DRAWING NO.		CODE NO.					1			
		ELC4- 276463		CL 550-0307-0					1			