APPLICA	BLE STANI	DARD									
	PATING TEMPERATURE RANGE STORAGE TEMPERATURE RANGE VOLTAGE CURRENT		-55 °C TO 85 °C (1) RAN		RANGE	RAGE HUMIDITY		40 % TO 80 %			
RATING			-10 °C TO 60 °C	-10 °C TO 60 °C (2) RAN				40 % TO 70 %			
			250 V AC			PLICABLE CABLE (AWG SIZE)		AWG22 TO 26			
			3 A		APPLICABLE CABLE (OUTER DIAMETER)			ϕ 1.0 TO 1.8mm			
SPECIFICATIONS											
IT	EM		TEST METHOD)			REQUI	REMENTS	QT	АТ	
CONSTRU	JCTION										
GENERAL EXAMINATION MARKING						ACCORDING TO DRAWING.				×	
ELECTRIC CHARACT		CONFIRMED VISUALLY.								×	
CONTACT R			100 mA (DC or 1000 Hz). 15 mΩ MAX .							l –	
ļ			CTERISTICS								
CONTACT INSERTION		□0.635±0.002mm BY STEEL GAUGE. INSERTION FORCE: 3.43 N MAX.							×	I —	
AND EXTRACTION FORCES					EX	EXTRACTION FORCE: 0.56 N MIN.					
MECHANICAL OPERATION		500 TIMES INSERTIONS AND EXTRACTIONS.			-	① CONTACT RESISTANCE: 15 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS				_	
						OF PARTS.					
ENVIRON	MENTAL C	HARAC	TERISTICS								
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY 48 h.			10	① CONTACT RESISTANCE: 15 mΩ MAX. ② NO HEAVY CORROSION.				_	
OTHERS											
CRIMP STRE	ENGTH				ΑV	VG26 :	24	N MIN.	×	T -	
COUN	INT DESCRIPTI		ON OF REVISIONS DESI		DESIGNE	SNED		CHECKED		TE	
REMARK			INCLUDED WHEN ENERGIZED.			APPROVED		HS. OKAWA	12. 1.	2. 20	
FOR THE UNUSED PRO			INDICATES A LONG-TERM STORAGE STATE SED PRODUCT BEFORE THE BOARD MOUNTED.			СН	IECKED	HT. YAMAGUCHI	12. 1.	2. 20	
						DES	SIGNED	KJ. NISHIWAKI	12. 1.	2. 19	
Unless ot	herwise spe	ecified, r	refer to MIL-STD-1344.			DRAWN		CR. TAKESHIMA	12. 1.	2. 19	
Note QT:Qı	st	DRA	WING N	IO.	ELC4-01684	ELC4-016842-02					
HRS.	SF	PECIFI	CATION SHEET		PART NO.			HIF3-2226SCA			
11.0	HIR	OSE E	LECTRIC CO., LTD.		CODE NO.		CL562	CL562-0244-2-00 🛕 1/1			