



May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





- Notes
- 1 SMT lead - coplanarity : 0.1 max.
 - 2 This product has no polarity to pattern for mounting.
 - 3 Emboss carrier tape package is applied on this product.
Please refer to the sheet 2/2 for the details.

2	Phosphor bronze	Contact area : Gold 0.1μm min	5	Polyester	(Top cover tape)
		Lead : Gold 0.05μm min	4	Polyethylene	(Emboss carrier tape)
		Under plating : Nickel 1μm min	3	Phosphor bronze	Tin - plating
1	LCP	Beige UL94V-0			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 4 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-F-00011032	
 HIROSE ELECTRIC CO., LTD.		APPROVED : KJ. KATAYOSE		20050105	DRAWING NO. EDC3-151990-01
		CHECKED : HS. OKAWA		20050105	PART NO. FX10B-144S-SV(21)
		DESIGNED : KT. DOI		20050105	CODE NO. CL0570-0253-8-21
		DRAWN : KT. DOI		20050105	
		DESIGNED : MT. ITANO		20211007	CHECKED : HT. YAMAGUCHI



Drawing for packing (2:1)



A (5:1)



Reeled dimension (Free)



- Notes
- 4 1 reel : 1,000 connectors.
 - 5 Minimum 10 compartments from both reel ends remain empty.
 - 6 This product has no polarity to tape and reel packaging.
 - 7 The dimensions in parentheses are for reference.

HRS

DRAWING NO.	EDC3-151990-01
PART NO.	FX10B-144S-SV(21)
CODE NO.	CL0570-0253-8-21

1/2