









May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE)



- NOTES 1 LEAD CO-PLANARITY SHALL BE 0.15 MAX.
2 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
3 IN CASE OF THE AUTOMATED MOUNTING, RECOMMENDED HOLE DIAMETER OF BOSS IS SHOWN IN FIG.1.

			3	BRASS	TIN-PLATING						
1	PPS	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.2#m min.						
					LEAD AREA:TIN-PLATING 2#m min.						
					UNDER PLATING:NICKEL 1.5#m min.						
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS					
UNITS mm				SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED :HS. OKAWA		07. 10. 19		DRAWING NO.		EDC3-082419-21			
		CHECED :HS. OZAWA		07. 10. 19		PART NO.		FX2-60S-1. 27SVL(71)			
		DESIGNED :SY. KAMIGA		07. 10. 19		CODE NO.		CL572-2155-2-71			
		DRAWN :HK. SUNADORI		07. 10. 19				 1/1			