May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

Main body



Protector



A-A (5:1)



B-B (5:1)









Assembly figure



Notes 1 The dimensions in parentheses are for reference.
△2 Once a connector is harnessed, the connector shall not be re-harnessed to a different cable.
Protectors shall also not be re-used once used in assembly.
When repair is needed, please replace the connector as well as all connector parts.

Re-using connector and connector parts may cause continuity failure due to
contact deformation / breakage, lock part destruction, etc.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
1	Beryllium copper	Over plated : Gold (Partially plating) Under Plated : Nickel	3	PBT	BLACK UL94V-0
			2	PBT	BLACK UL94V-0

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△1	1	DIS-F-00005561	AK. IWAHORI	HT. YAMAGUCHI	20200218

HIROSE ELECTRIC CO., LTD.

APPROVED	HT. YAMAGUCHI	20180625
CHECKED	HT. YAMAGUCHI	20180625
DESIGNED	HR. NAGAYASU	20180622
DRAWN	MK. OOKI	20180621

DRAWING NO.	EDC-017339-11-02
PART NO.	HIF3BA-26D-2.54R(11)
CODE NO.	CL610-0025-8-11

△1 1/1

HRS DRAWING FOR REFERENCE