Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



Recommended PC board hole pattern

Mating side







Notes 1 The upper row dimension shows when the lock open out.
2 The dimensions in parentheses are for reference.
△1 3 UL(File No. E52653)
C-UL(File No. E52653) authorization article.

NO.	MATERIAL	FINISH , REMARKS
3	STAINLESS	
2	PBT	BLACK UL94V-0
1	PBT	BLACK UL94V-0

NO.	MATERIAL	FINISH , REMARKS
5	BRASS	Contact area : Gold 0.2μm min Dip area : TIN-Plating 2μm min Under plating : Nickel 2.5μm min
4	BRASS	Contact area : Gold 0.2μm min Dip area : TIN-Plating 2μm min Under plating: Nickel 2.5μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△1	1	DIS-F-00005872	AK. IWAHORI	HT. YAMAGUCHI	20200221

HIROSE ELECTRIC CO., LTD.

APPROVED	HT. YAMAGUCHI	20181210	DRAWING NO. EDC-016932-63-00
CHECKED	HT. YAMAGUCHI	20181210	PART NO. HIF3B-26PA-2.54DS(63)
DESIGNED	TS. OONO	20181207	
DRAWN	MK. OOKI	20181207	CODE NO. CL610-0054-6-63 △1 1/1

HRS DRAWING FOR REFERENCE