






Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



Recommended PC board hole pattern



- Notes 1 The upper dimension shows when the lock open out.
2 The dimensions in parentheses are for reference.
3 UL(File No.E52653) authorization article.



3	STAINLESS			4	BRASS	Contact area : Gold 0.2μm min.
2	PBT	BLACK	UL94V-0			Dip area : TIN-Plating 2μm min.
1	PBT	BLACK	UL94V-0			Under plating: Nickel 2.5μm min.
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS
UNITS mm		SCALE 2 : 1	COUNT 1	DESCRIPTION OF REVISIONS		DESIGNED AK. IWAHORI
HIROSE ELECTRIC CO., LTD.		APPROVED : HT. YAMAGUCHI	20181210	DRAWING NO. EDC-019355-63-00		
		CHECKED : HT. YAMAGUCHI	20181210	PART NO. HIF3CA-10PA-2.54DSA(63)		
		DESIGNED : HR. NAGAYASU	20181207	CODE NO. CL610-0701-1-63		
		DRAWN : TS. HORI	20181207			
						DATE 20200309