May.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE



Recommended PC board hole pattern







Notes 1 The upper row dimension shows when the lock open out.
2 The dimensions in parentheses are for reference.
⚠1 3 UL(File No. E52653)
C-UL(File No. E52653) authorization article.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	STAINLESS		4	BRASS	Contact area : Gold 0.15μm min
2	PBT	BLACK UL94V-0			Dip area : TIN-Plating 2μm min
1	PBT	BLACK UL94V-0			Under plating : Nickel 2.5μm min

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	⚠1	1	DIS-F-00005921	AK. IWAHORI	HT. YAMAGUCHI	20200306

HIROSE ELECTRIC CO., LTD.

APPROVED	HT. YAMAGUCHI	20181210	DRAWING NO. EDC-361214-63-00
CHECKED	HT. YAMAGUCHI	20181210	PART NO. HIF3MAW-50PA-2.54DSA(63)
DESIGNED	HR. NAGAYASU	20181207	
DRAWN	TS. HORI	20181207	CODE NO. CL610-3609-5-63 ⚠1 1/1