APPLICA	BLE STANI	DARD									
	OPERATING				STOF						
RATING	TEMPERATURE RANGE		-55 °C TO 85 °C (1)				JRE RANGE		-10 °C TO 60 °C (2)		
	VOLTAGE		200 V AC		RANG				40 % TO 80 %		
	CURRENT		1 A	STC		RAGE HUMIDITY			40 % TO 70 % ⁽²⁾		
			SPEC	IFICA	TION						
ITEM			TEST METHOD			REQUIREMENTS				QT	ΔТ
CONSTRUCTION		TEST MIETTION				THE CONTENTS				١٠٠	Α.
		MISHALL	Y AND BY MEASURING INS	STRUMEN	NT I	ACCOF	RDING TO) DR	AWING	×	×
MARKING		CONFIRMED VISUALLY.				A0001	(DINO IV	O DIN	AVVIIVO.	⊢^ ×	×
ELECTRIC CHARAC											
CONTACT RESISTANCE		100 mA (DC or 1000 Hz).				15 mΩ MAX.					Ι_
INSULATION		500 V DC.				1000 MΩ MIN.				×	+=
RESISTANCE		300 V DC.				TOOO IVI SZ IVIIIN.				^	
VOLTAGE PROOF		650 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				×	-
MECHANI	CAL CHAR	ACTERI	STICS		1					l .	
MECHANIC/			S INSERTIONS AND EXTR	ACTIONS	S. T	① COI	NTACT R	ESIS	TANCE: 15 mΩ MAX.	×	_
OPERATION						② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.					
VIBRATION		FREQUENCY 10 TO 55 Hz,				 NO ELECTRICAL DISCONTINUITY OF μs. NO DAMAGE, CRACK AND LOOSENESS 				×	_
		AMPLITUDE : 1.5 mm,									
		AT 2 h FOR 3 DIRECTION.									
SHOCK		490 m/s ² , DURATION OF PULSE 11 ms				OF PARTS.				×	-
ENIV (IDON	NACNITAL O		TIMES FOR 3 DIRECT	IONS.							
	MENTAL C							==:=			
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.				① CONTACT RESISTANCE: 15 mΩ MAX. ② INSULATION RESISTANCE:1000 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS				×	-
RAPID CHANGE OF		TEMPERATURE-65→+15~+35→+125→+15~+35°C								×	+-
TEMPERATURE		TIME $30 \rightarrow 10 \sim 15 \rightarrow 30 \rightarrow 10 \sim 15 \text{ min}$					PARTS.	=, CR	ACK AND LOOSENESS	^	
			5 CYCLES.	10 10		0,	. ,				
CORROSION SALT MIST						 CONTACT RESISTANCE: 15 mΩ MAX. NO HEAVY CORROSION. 				×	_
HYDROGEN SULPHIDE		48 h. EXPOSED IN 3 PPM FOR 120 h.								×	-
HIDROGEN SOLFHIDE		EXPOSED IN 3 PPM FOR 120 h.								^	
RESISTANCE TO SOLDERING HEAT		' '				NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.				×	_
		260±5°C FOR IMMERSION, DURATION, 10±1s. 2) SOLDERING IRONS: 360°C FOR 5 s MAX.									-
		(2) SOLDI	ERING IRONS : 300 C FOR	S S IVIAA.	•	· · · · · · · · · · · · · · · · · ·	117 (20.			×	
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE,				A NEW UNIFORM COATING OF SOLDER				×	l _
		245±3°C, FOR IMMERSION DURATION, 2 s.				SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.					
COUN	IT D	DESCRIPTION OF REVISIONS DE		DESIC	 GNED			CHECKED		TE.	
<u> </u>		DESCRIPTION OF REVIOURS		DESIG	- IOINED		CHECKED		DA	1 =	
	(1) TEMPER ATUS	DE DISCUN						<u>/ED</u>	ED LIG ON YMY		0.00
			NCLUDED WHEN ENERGIZED. TES A LONG-TERM STORAGE STATE DDUCT BEFORE THE BOARD MOUNTED.			CHECKED		-	·		8. 28
									HS. OZAWA	07.0	
Halana attennista - 15° 1			refer to MIL CTD 200			DESIGNED		-	KY. NAKAMURA		
Unless otherwise specified, r			refer to MIL-STD-202.				DRAW	/N	TP. MATSUMOTO	07.0	8. 27
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DF	RAWING NO. ELC4-016897-				-21	
SPECIFICATION SHEET HIPOSE ELECTRIC CO. LTD. 2008					PART	NO. HIF3E-10PA-2. 54DS (71)					
HIROSE E			LECTRIC CO., LTD. CO			E NO. CL614-0041-0-71			-0041-0-71	<u> </u>	1/1
ORM HD0011-	-2-1								<u> </u>		