


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .




RECOMMENDED PC BOARD HOLE PATTERN









HRS DRAWING FOR REFERENCE

PART No.	HRS No.	PIN	A	B	C	D	2 POLARIZING KEY MOUNT
HIF3FC- 10PA-2.54DS(71)	CL616-0061-0-71	10	20.2	17.5	10.16	4.1	NONE
HIF3FC- 14PA-2.54DS(71)	CL616-0062-2-71	14	25.28	22.58	15.24	4.1	1 ON RIGHT SIDE
HIF3FC- 16PA-2.54DS(71)	CL616-0063-5-71	16	27.82	25.12	17.78	4.1	
HIF3FC- 20PA-2.54DS(71)	CL616-0064-8-71	20	32.9	30.2	22.86	4.1	
HIF3FC- 26PA-2.54DS(71)	CL616-0065-0-71	26	40.52	37.82	30.48	4.1	
HIF3FC- 30PA-2.54DS(71)	CL616-0066-3-71	30	45.6	42.9	35.56	4.1	1 EACH ON LEFT & RIGHT SIDE.
HIF3FC- 34PA-2.54DS(71)	CL616-0067-6-71	34	50.68	47.98	40.64	4.1	
HIF3FC- 40PA-2.54DS(71)	CL616-0068-9-71	40	58.3	55.6	48.26	4.1	
HIF3FC- 50PA-2.54DS(71)	CL616-0069-1-71	50	71.0	68.3	60.96	4.1	
HIF3FCA-50PA-2.54DS(71)	CL616-0070-0-71	50	71.0	68.3	60.96	26.96	

NOTE 1 THE 10 CONTACT TYPE HAS NO STAND OFF AT THE CENTER.
2 THE NUMBER OF POLARIZING KEY MOUNTS DEFFERS AS TO THE NUMBER OF PINS, REFER TO THE TABLE.
3 ** INDICATES THE NUMBER OF CONTACT.
4 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
1	PBT	BLACK, UL94 V-0	2.3	BRASS	CONTACT AREA:GOLD 0.2μm min. DIP AREA:TIN-PLATING 2μm min. UNDER PLATING:NICKEL 2μm min.

CODE NO.(OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL	A.SUZUKAWA '06.05.08	H.Nakamura '06.05.10	K.Ojima '06.05.10	H.Ekawa '06.05.10	

SCALE	DRAWING NO.	PART NO.
FREE	EDC3-151846-21	HIF3FC-**PA-2.54DS(71)
UNITS: mm	HIROSE ELECTRIC CO., LTD	CODE NO. CL616 — 1/1

TO
PCK

FORM NO.229