Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| | | | | |
|---|---|---|---|---|
| APPLICABLE STANDARD | | UL:UL1977 | | |
| RATING | OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C (1) | STORAGE TEMPERATURE RANGE | -10 °C TO 60 °C (2) |
| | VOLTAGE | 300 V AC | OPERATING HUMIDITY RANGE | RELATIVE HUMIDITY 85% MAX (NOT DEWED) |
| | CURRENT | 3 A | STORAGE HUMIDITY RANGE | |
| UL RATING | VOLTAGE | 250 V AC | | |
| | CURRENT | 1 A | | |

## SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|---|---|---|---|---|
| **CONSTRUCTION** | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | × | × |
| MARKING | CONFIRMED VISUALLY. | | × | × |
| **ELECTRIC CHARACTERISTICS** | | | | |
| CONTACT RESISTANCE | 100 mA (DC OR 1000 Hz). | 15 mΩ MAX. | × | — |
| INSULATION RESISTANCE | 500 V DC | 1000 MΩ MIN. | × | — |
| VOLTAGE PROOF | 1000 V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | × | — |
| **MECHANICAL CHARACTERISTICS** | | | | |
| CONTACT INSERTION AND EXTRACTION FORCES | □0.635±0.002mm BY STEEL GAUGE. | INSERTION FORCE: 4.4 N MAX.<br>EXTRACTION FORCE: 0.56 N MIN. | × | — |
| MECHANICAL OPERATION | 500 TIMES INSERTIONS AND EXTRACTIONS. | ①CONTACT RESISTANCE: 15 mΩ MAX.<br>②NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × | — |
| VIBRATION | FREQUENCY 10 TO 55 Hz,<br>AMPLITUDE : 1.5 mm,<br>AT 2 h FOR 3 DIRECTIONS. | ①NO ELECTRICAL DISCONTINUITY OF 1 μs.<br>②NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × | — |
| SHOCK | 490 m/s$^2$ , DURATION OF PULSE 11 ms<br>AT 3 TIMES FOR 3 DIRECTIONS. | | × | — |
| **ENVIRONMENTAL CHARACTERISTICS** | | | | |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40±2 °C, 90 ～ 95 %, 96 h. | ①CONTACT RESISTANCE: 15 mΩ MAX.<br>②INSULATION RESISTANCE:1000 MΩ MIN.<br>③NO DAMAGE, CRACK AND LOOSENESS OF PARTS. | × | — |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE-55→+15～+35→+125→+15～+35°C<br>TIME 30 → 10～15 → 30 → 10～15 min.<br>UNDER 5 CYCLES. | | × | — |
| CORROSION SALT MIST | EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h. | ①CONTACT RESISTANCE: 15 mΩ MAX.<br>②NO HEAVY CORROSION. | × | — |
| SULPHUR DIOXIDE | EXPOSED IN 3 PPM FOR 96 h.<br>(TEST STANDARD: JEIDA – 38) | | × | — |
| RESISTANCE TO SOLDERING HEAT | 1) SOLDER BATH:SOLDER TEMPERATURE, 260±5℃ FOR IMMERSION,DURATION,10±1s. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | × | — |
| | 2) SOLDERING IRONS : 360℃ FOR 5 s MAX. | | × | — |
| SOLDERABILITY | SOLDERED AT SOLDER TEMPERATURE, 245±3°C,<br>FOR IMMERSION DURATION, 2 s. | A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED. | × | — |

| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|---|---|---|---|---|---|
| 1 | 2 | DIS-F-00005942 | AK. IWAHORI | HT. YAMAGUCHI | 20200313 |

REMARK (1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED.
(2) THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.

Unless otherwise specified, refer to MIL-STD-202.

| | | |
|---|---|---|
| APPROVED | HT. YAMAGUCHI | 20181210 |
| CHECKED | HT. YAMAGUCHI | 20181210 |
| DESIGNED | HR. NAGAYASU | 20181207 |
| DRAWN | TS. HORI | 20181207 |

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC-386221-00-00

HRS

SPECIFICATION SHEET

HIROSE ELECTRIC CO., LTD.

PART NO. HIF3H-*DA-2.54DSA(61)

CODE NO. 1 1/1

FORM HD0011-2-1