

1 2 3 4 5 6 7 8

A

B

C

D

E

F

A




B

C


D

E

F



RECOMMENDED PC BOARD HOLE PATTERN
(PCB THICKNESS : t=1.6)



PART NO.	CODE NO.	PIN	A	B
A4B- 2PA-2DSA(51)	CL622-0401-8-51	2	4	2
A4B- 3PA-2DS(A51)	CL622-0402-0-51	3	6	4
A4B- 4PA-2DSA(51)	CL622-0403-3-51	4	8	6
A4B- 5PA-2DSA(51)	CL622-0404-6-51	5	10	8
A4B- 6PA-2DSA(51)	CL622-0405-9-51	6	12	10
A4B- 7PA-2DSA(51)	CL622-0406-1-51	7	14	12
A4B- 8PA-2DSA(51)	CL622-0407-4-51	8	16	14
A4B- 9PA-2DSA(51)	CL622-0408-7-51	9	18	16
A4B-10PA-2DSA(51)	CL622-0409-0-51	10	20	18
A4B-12PA-2DSA(51)	CL622-0411-1-51	12	24	22
A4B-13PA-2DSA(51)	CL622-0412-4-51	13	26	24
A4B-14PA-2DSA(51)	CL622-0413-7-51	14	28	26
A4B-15PA-2DSA(51)	CL622-0414-0-51	15	30	28
A4B-16PA-2DSA(51)	CL622-0415-2-51	16	32	30

1		POLYAMIDE		BLACK UL94V-0		2		BRASS		CONTACT AREA : GOLD FLASH	
NO.		MATERIAL		FINISH . REMARKS		NO.		MATERIAL		DIP AREA : TIN-PLATING 2μm	
UNITS mm				SCALE 5 : 1		COUNT 		DESCRIPTION OF REVISIONS		DESIGNED	
HRS		HIROSE ELECTRIC CO., LTD.		APPROVED : NH. NAKATA 17. 04. 10		CHECKED : HT. YAMAGUCHI 17. 04. 10		DRAWING NO. EDC-375932-00-00		CHECKED	
				DESIGNED : HR. NAGAYASU 17. 04. 10		DRAWN : HR. NAGAYASU 17. 04. 10		PART NO. A4B- * PA-2DSA(51)		DATE	
								CODE NO. CL622		1/1	

FORM HC0011-5-7 1 2 3 4 5 6 7 8