

APPLICABLE STANDARD																													
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C																									
	VOLTAGE	AC 100 V	OPERATING HUMIDITY RANGE	RELATIVE HUMIDITY: 95% MAX (NO DEW CONDENSATION IS PERMITTED)																									
	CURRENT	SIGNAL: 0.5A																											
SPECIFICATIONS																													
ITEM		TEST METHOD	REQUIREMENTS	QT	AT																								
CONSTRUCTION																													
GENERAL EXAMINATION		VISUAL AND WITH MEASURING INSTRUMENT	ACCORDING TO A DRAWING	X	X																								
MARKING		CONFIRM VISUALLY		X	X																								
ELECTRIC CHARACTERISTICS																													
CONTACT RESISTANCE [EIA-364-23]		100 mA	50 mΩ MAX (*1) MATED WITH ER8-10P-0.8SV-*H(**)	X	—																								
INSULATION RESISTANCE [EIA-364-21]		100 V DC	1000 MΩ MIN	X	—																								
VOLTAGE PROOF [EIA-364-20]		300 V AC FOR 1 min	NO FLASHOVER OR BREAKDOWN	X	—																								
MECHANICAL CHARACTERISTICS																													
MECHANICAL OPERATION [EIA-364-09]		100 TIMES INSERTION AND EXTRACTION	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS 2) NO FLASHOVER OR BREAKDOWN 3) NO DAMAGE, CRACK OR LOOSENESS OF PARTS	X	—																								
RANDOM VIBRATION [EIA-364-28]		FREQUENCY: 20 TO 500 Hz POWER SPECTRAL DENSITY: 0.02 G ² /Hz FOR 90 min IN THREE DIRECTIONS	1) NO ELECTRICAL DISCONTINUITY OF 1 μs OR MORE 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS	X	—																								
SHOCK [EIA-364-27]		980 m/s ² , DURATION OF PULSE: 6 ms 18TIMES TOTAL, 3 EACH DIRECTION, 3 AXIS		X	—																								
ENVIRONMENTAL CHARACTERISTICS																													
THERMAL SHOCK [EIA-364-32]		TEMPERATURE(°C): -55 →20 ~ 35 → 85 →20 ~ 35 TIME(min): 30 → 2 ~ 3 → 30 →2 ~ 3 UNDER 25 CYCLES	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS	X	—																								
CYCLIC TEMPERATURE AND HUMIDITY [EIA-364-31]		@ 25 °C, 90-95% RH: 120 min DWELL TIME ↑ ↓ 120min RAMP TIME @ 65 °C, 90-95% RH: 120 min DWELL TIME UNDER 12CYCLES	3) NO FLASHOVER OR BREAKDOWN 4) INSURATION RESISTANCE:1000MΩ MIN	X	—																								
DRY HEAT [EIA-364-17]		EXPOSED AT 105 °C, 250 HOURS	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS	X	—																								
GAS TIGHT [EIA-364-36]		Nitric acid vapor 60min		X	—																								
<table><tr><td></td><td>COUNT</td><td>DESCRIPTION OF REVISIONS</td><td>DESIGNED</td><td>CHECKED</td><td>DATE</td></tr><tr><td colspan="3">REMARK (*1) THE VALUE OF CONTACT RESISTANCE INCLUDES THE BULK RESISTANCE.</td><td>APPROVED</td><td>MK. EZAKI</td><td>16.06.14</td></tr><tr><td colspan="3" rowspan="3">Unless otherwise specified, refer to IEC 60512.</td><td>CHECKED</td><td>MK. EZAKI</td><td>16.06.14</td></tr><tr><td>DESIGNED</td><td>TF. SUGAWARA</td><td>16.06.14</td></tr><tr><td>DRAWN</td><td>TF. SUGAWARA</td><td>16.06.14</td></tr></table>							COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	REMARK (*1) THE VALUE OF CONTACT RESISTANCE INCLUDES THE BULK RESISTANCE.			APPROVED	MK. EZAKI	16.06.14	Unless otherwise specified, refer to IEC 60512.			CHECKED	MK. EZAKI	16.06.14	DESIGNED	TF. SUGAWARA	16.06.14	DRAWN	TF. SUGAWARA	16.06.14
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE																								
REMARK (*1) THE VALUE OF CONTACT RESISTANCE INCLUDES THE BULK RESISTANCE.			APPROVED	MK. EZAKI	16.06.14																								
Unless otherwise specified, refer to IEC 60512.			CHECKED	MK. EZAKI	16.06.14																								
			DESIGNED	TF. SUGAWARA	16.06.14																								
			DRAWN	TF. SUGAWARA	16.06.14																								
NOTE -- QT: QUALIFICATION TEST; AT: ASSURANCE TEST; X: APPLICATION TEST			DRAWING NO.		ELC-361704-00-00																								
	SPECIFICATION SHEET		PART NO.	ER8-10S-0.8SV-5H																									
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL625-0007-5-00	1/1																								