






APPLICABLE STANDARD																																			
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C																															
	VOLTAGE	AC 100 V	OPERATING HUMIDITY RANGE	RELATIVE HUMIDITY: 95% MAX (NO DEW CONDENSATION IS PERMITTED)																															
	CURRENT	SIGNAL: 0.5A																																	
SPECIFICATIONS																																			
ITEM		TEST METHOD	REQUIREMENTS	QT	AT																														
CONSTRUCTION																																			
GENERAL EXAMINATION		VISUAL AND WITH MEASURING INSTRUMENT	ACCORDING TO A DRAWING	X	X																														
MARKING		CONFIRM VISUALLY		X	X																														
ELECTRIC CHARACTERISTICS																																			
CONTACT RESISTANCE [EIA-364-23]		100 mA	50 mΩ MAX (*1) MATED WITH ER8-100P-0.8SV-**H(**)	X	—																														
INSULATION RESISTANCE [EIA-364-21]		100 V DC	1000 MΩ MIN	X	—																														
VOLTAGE PROOF [EIA-364-20]		300 V AC FOR 1 min	NO FLASHOVER OR BREAKDOWN	X	—																														
MECHANICAL CHARACTERISTICS																																			
MECHANICAL OPERATION [EIA-364-09]		100 TIMES INSERTION AND EXTRACTION	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS 2) NO FLASHOVER OR BREAKDOWN 3) NO DAMAGE, CRACK OR LOOSENESS OF PARTS	X	—																														
RANDOM VIBRATION [EIA-364-28]		FREQUENCY: 20 TO 500 Hz POWER SPECTRAL DENSITY: 0.02 G <sup>2</sup> /Hz FOR 90 min IN THREE DIRECTIONS	1) NO ELECTRICAL DISCONTINUITY OF 1 μs OR MORE 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS	X	—																														
SHOCK [EIA-364-27]		980 m/s <sup>2</sup> , DURATION OF PULSE: 6 ms 18TIMES TOTAL, 3 EACH DIRECTION, 3 AXIS		X	—																														
ENVIRONMENTAL CHARACTERISTICS																																			
THERMAL SHOCK [EIA-364-32]		TEMPERATURE(°C): -55 →20 ~ 35 → 85 →20 ~ 35 TIME(min): 30 → 2 ~ 3 → 30 →2 ~ 3 UNDER 25 CYCLES	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS 2) NO DAMAGE, CRACK OR LOOSENESS OF PARTS	X	—																														
CYCLIC TEMPERATURE AND HUMIDITY [EIA-364-31]		@ 25 °C, 90-95% RH: 120 min DWELL TIME ↑ ↓ 120min RAMP TIME @ 65 °C, 90-95% RH: 120 min DWELL TIME UNDER 12CYCLES	3) NO FLASHOVER OR BREAKDOWN 4) INSURATION RESISTANCE:1000MΩ MIN	X	—																														
DRY HEAT [EIA-364-17]		EXPOSED AT 105 °C, 250 HOURS	1) CONTACT RESISTANCE CHANGE: 15 mΩ OR LESS	X	—																														
GAS TIGHT [EIA-364-36]		Nitric acid vapor 60min		X	—																														
<table><tr><td></td><td>COUNT</td><td>DESCRIPTION OF REVISIONS</td><td>DESIGNED</td><td>CHECKED</td><td>DATE</td></tr><tr><td colspan="3">REMARK (*1) THE VALUE OF CONTACT RESISTANCE INCLUDES THE BULK RESISTANCE.</td><td>APPROVED</td><td>TY. TAKADA</td><td>20231128</td></tr><tr><td colspan="3"></td><td>CHECKED</td><td>TY. TAKADA</td><td>20231128</td></tr><tr><td colspan="3"></td><td>DESIGNED</td><td>SHAOLONG WU</td><td>20231128</td></tr><tr><td colspan="3">Unless otherwise specified, refer to IEC 60512.</td><td>DRAWN</td><td>SHAOLONG WU</td><td>20231128</td></tr></table>							COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	REMARK (*1) THE VALUE OF CONTACT RESISTANCE INCLUDES THE BULK RESISTANCE.			APPROVED	TY. TAKADA	20231128				CHECKED	TY. TAKADA	20231128				DESIGNED	SHAOLONG WU	20231128	Unless otherwise specified, refer to IEC 60512.			DRAWN	SHAOLONG WU	20231128
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE																														
REMARK (*1) THE VALUE OF CONTACT RESISTANCE INCLUDES THE BULK RESISTANCE.			APPROVED	TY. TAKADA	20231128																														
			CHECKED	TY. TAKADA	20231128																														
			DESIGNED	SHAOLONG WU	20231128																														
Unless otherwise specified, refer to IEC 60512.			DRAWN	SHAOLONG WU	20231128																														
NOTE -- QT: QUALIFICATION TEST; AT: ASSURANCE TEST; X: APPLICATION TEST			DRAWING NO.	ELC-369155-00-00																															
	SPECIFICATION SHEET		PART NO.	ER8-100S-0.8SV-7H																															
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0625-0044-0-00	 1/1																														