


Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.









RECOMMENDED PATTERN(5:1)
(RECOMMENDED BOARD THICKNESS t=1.6mm)

HRS DRAWING FOR REFERENCE

APRICATION DIAGRAM





PART No.	CODE No.	THE NUMBER OF CONTACT	A	B	C	D	E
DF33C-2P-3.3DSA(24)	CL676-1131-2-24	2	8.4	—	2.5	3.5	6.8
DF33C-3P-3.3DSA(24)	CL676-1132-5-24	3	11.7	6.6	2.5	3.5	6.8
DF33C-4P-3.3DSA(24)	CL676-1133-8-24	4	15.0	9.9	5.1	6.1	10.15
DF33C-5P-3.3DSA(24)	CL676-1134-0-24	5	18.3	13.2	5.1	6.1	10.15
DF33C-6P-3.3DSA(24)	CL676-1135-3-24	6	21.6	16.5	5.1	6.1	10.15

NOTES 1 :IMMERSION DEPTH INTO POTTIING SOLUTION:6.5mm
2 :FORCEFULLY UNMATING THE CONNECTORS WILL RISK DAMAGING THEM: THEREFORE, WHEN IT IS DIFFICULT TO UNMATE A CONNECTOR, FIRST GENTLY PRESS DOWN ON IT, THEN RELEASE THE LOCK TO ALLOW REMOVAL.

NO.	MATERIAL	FINISH , REMARKS
1	⚠1 PBT	⚠1 WHITE, UL94V-0
2	BRASS	SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL PLATED 0.5μm min
3	HIPS	TRAY

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	⚠1	2	DIS-H-00012938	SS. YAMASAKI	SZ. ONO	20220323


HIROSE ELECTRIC CO., LTD.


APPROVED	KI. AKIYAMA	20131217
CHECKED	HK. UMEHARA	20131217
DESIGNED	HT. SATO	20131217
DRAWN	MI. SAKIMURA	20131217

DRAWING NO.	EDC3-354785-01
PART NO.	DF33C-*P-3.3DSA(24)
CODE NO.	CL676- ⚠1 1/1

Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE





PART No.	CODE No.	THE NUMBER OF TRAY PACKING
DF33C-2P-3.3DSA(24)	CL676-1131-2-24	135
DF33C-3P-3.3DSA(24)	CL676-1132-5-24	95
DF33C-4P-3.3DSA(24)	CL676-1133-8-24	75
DF33C-5P-3.3DSA(24)	CL676-1134-0-24	60
DF33C-6P-3.3DSA(24)	CL676-1135-3-24	50

NOTES 2 :MINIMUM UNIT OF PURCHASE SHALL BE THE QUANTITY OF CONNECTORS IN TRAY.

HRS	DRAWING NO.	EDC3-354785-01
	PART NO.	DF33C-*P-3.3DSA(24)
	CODE NO.	CL676- 1/1